



SINGLE-SPLIT WALL MOUNTED TYPE

Standard Series **SRK-ZSP-W**

NEW



SRK25ZSP-W, SRK35ZSP-W, SRK45ZSP-W



SRK-ZSP-W series can be selected for use both R32 and R410A outdoor unit.




Wireless remote control



SRC25ZSP-W
SRC35ZSP-W



SRC45ZSP-W



Elegant Timeless Design

ZSP series is elegant design fits into any kind of interior decoration.

Energy Class Improvement

All class **A++**

Compact and Light weight

The SRK-ZSP-W series offers great installation flexibility.

FUNCTIONS

Energy saving

Air flow

Clean operation & Filter



Comfort & Convenience

Others



SPECIFICATIONS

Indoor unit			SRK25ZSP-W	SRK35ZSP-W	SRK45ZSP-W
Outdoor unit			SRC25ZSP-W	SRC35ZSP-W	SRC45ZSP-W
Power source			1 Phase, 220 - 240V, 50Hz		
Nominal cooling capacity (Min~Max)		kW	2.5(0.9~3.1)	3.2(0.9~3.7)	4.5(1.3~4.8)
Nominal heating capacity (Min~Max)		kW	2.8(1.0~4.1)	3.6(1.0~4.6)	5.0(1.2~5.8)
Power consumption		kW	Cooling/Heating	0.910 / 0.930	1.350 / 1.360
EER/COP			Cooling/Heating	3.52/4.05	3.52 / 3.87
Max. running current		A	9	9	14.5
Sound power level	Indoor	Cooling/Heating	57 / 57	58 / 58	56 / 62
	Outdoor	Cooling/Heating	57 / 56	59 / 60	63 / 64
Sound pressure level	Indoor	Cooling (Hi/Me/Lo)	45 / 34 / 23	45 / 36 / 23	44 / 39 / 24
		Heating (Hi/Me/Lo)	43 / 34 / 26	44 / 36 / 28	48 / 41 / 30
	Outdoor	Cooling/Heating	47 / 45	48 / 48	51 / 51
		Air flow	Indoor	Cooling (Hi/Me/Lo)	10.0 / 7.3 / 4.2
Exterior dimensions	Indoor / Outdoor	HeightxWidthxDepth	mm	267 x 783 x 210	
				540 x 645(+57) x 275	
				595 x 780(+62) x 290	
Net weight		kg	7.0 / 26.5	7.0 / 28.5	7.5 / 36.0
Refrigerant		Type/GWP	R32 / 675		
		Charge	0.550 / 0.371	0.68 / 0.459	1.10 / 0.743
Refrigerant piping size		Liquid/Gas	ø mm		6.35(1/4") / 9.52(3/8")
Refrigerant line (one way) length		m	Max. 15		
Vertical height differences		Outdoor is higher/lower	m		Max. 10 / Max. 10
Outdoor operating temperature range		Cooling	-15~46		
		Heating	-15~24		
Clean filter			-		

* The data are measured under the following conditions(ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

* Sound level indicates the value in anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

* 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.