# Embraco Condensing Unit R404a LBP 8.77CC Nominal Capacity 490W

Product Code: UNEK2134GK FL

#### **PRODUCT DESCRIPTION**

r404a 220-240v50hz max amb 43c 1/2+hp 474w evap-25c amb32c sub3k gas32c 465 d x 340 w x 296 mmh. 3/8",1/4" flare bracket mounted valves, 1.1I receiver

Full range from 1/7 Hp up to 1,5 Hp for R-134a, R-404A and R-290 applications.

Different configurations available: with/without Service Valves (suction/discharge) and with/without Liquid Receiver. Various options available: Liquid Line, Shrader Valve on process port, Pressure Control, Double Fan Condenser, etc...) Gemini version with double compressor available too.

#### **UNEK Features and Benefits**

- Low sound level
- Low vibrations
- High reliability in severe working conditions

Application: LBP, M/HBP for R-134a, R-404A and R-290

Compressors from 7,3cc to 16,8cc

# Embraco Condensing Unit R404a LBP 17.39CC Nominal Capacity 910W

Product Code: UNT2178GK FL

#### PRODUCT DESCRIPTION

r404a lbp 220-240v 50hz csir 17.39cc 835w @ -23.3/32c evap/amb complete with receiver and valves flare

## Full range from 1/7 Hp up to 1,5 Hp for R-134a, R-404A and R-290 applications.

Different configurations available: with/without Service Valves (suction/discharge) and with/without Liquid Receiver. Various options available: Liquid Line, Shrader Valve on process port, Pressure Control, Double Fan Condenser, etc...) Gemini version with double compressor available too.

#### **UNT Features and Benefits**

- High efficiency level
- High cooling capacity at low evaporating temperatures
- Very low sound level

Application: LBP, M/HBP for R-134a and R-404A

Compressors from 12,6cc to 22,4cc

# Embraco Condensing Unit R404a LBP 20.44CC Nominal Capacity 935W

Product Code: UNT2180GK ODS

#### **PRODUCT DESCRIPTION**

r404a lbp 220-240v 50hz csir 20.44cc 980w @ -23.3/32c evap/amb complete with receiver and valves ods

### Full range from 1/7 Hp up to 1,5 Hp for R-134a, R-404A and R-290 applications.

Different configurations available: with/without Service Valves (suction/discharge) and with/without Liquid Receiver. Various options available: Liquid Line, Shrader Valve on process port, Pressure Control, Double Fan Condenser, etc...) Gemini version with double compressor available too.

#### **UNT Features and Benefits**

- High efficiency level
- High cooling capacity at low evaporating temperatures
- Very low sound level

Application: LBP, M/HBP for R-134a and R-404A

Compressors from 12,6cc to 22,4cc

### Embraco Condensing Unit R404a LBP 27.8CC Nominal Capacity 1056W

Product Code: UNT2212GK FL

#### PRODUCT DESCRIPTION

r404a lbp 220-240v 50hz csr 27.8cc 1371w @ -23.3/32c evap/amb complete with receiver and valves flare

### Full range from 1/7 Hp up to 1,5 Hp for R-134a, R-404A and R-290 applications.

Different configurations available: with/without Service Valves (suction/discharge) and with/without Liquid Receiver. Various options available: Liquid Line, Shrader Valve on process port, Pressure Control, Double Fan Condenser, etc...) Gemini version with double compressor available too.

#### **UNT Features and Benefits**

- High efficiency level
- High cooling capacity at low evaporating temperatures
- Very low sound level

Application: LBP, M/HBP for R-134a and R-404A

Compressors from 12,6cc to 22,4cc

### Embraco Condensing Unit R404a LBP 34.38CC Nominal Capacity 1599W

Product Code: UNJ2212GK ODS

#### **PRODUCT DESCRIPTION**

r404a lbp 220-240v 50hz csr 34.38cc 1544w @ -23.3/32c evap/amb complete with receiver and valves ods

## Full range from 1/7 Hp up to 1,5 Hp for R-134a, R-404A and R-290 applications.

Different configurations available: with/without Service Valves (suction/discharge) and with/without Liquid Receiver. Various options available: Liquid Line, Shrader Valve on process port, Pressure Control, Double Fan Condenser, etc...) Gemini version with double compressor available too.

#### **UNJ Features and Benefits**

- Small size platform
- High energy efficiency
- Reduced noise level

Application: LBP, M/HBP for R-134a and R-404A

Compressors from 21,7cc to 34,4cc