



## CONSTRUCTION PRODUCTS REGULATION DECLARATION of PERFORMANCE

<b>Product Identification:</b>	<b>Multipanel® 11mm Laminate faced wall panel Collections</b>
<b>Type:</b>	All standard grades
<b>Intended use:</b>	Wood-based panels for use in construction – Characteristics, evaluation of conformity and marking
<b>Manufacturer address:</b>	Grant Westfield Westfield Avenue Edinburgh United Kingdom EH11 2QH
<b>System of Assessment and Verification of Constancy of Performance (AVCP):</b>	<b>System 4</b>
<b>Provisions:</b>	<b>EN 13986:2004</b> Wood-based panels for use in construction – Characteristics, evaluation of conformity and marking
	<b>EN 622-5:2009</b> Meditate exterior grade MDF for use in humid conditions
	<b>EN 438-3:2005</b> High-pressure decorative laminates (HPL). Sheets based on thermosetting resins (usually called laminates). Classification and specifications for laminates less than 2mm thick intended for bonding to supporting substrates

Essential Characteristics:	Test Method	Standard	Measure
<b>Bonding Strength</b>	EN 319	EN 622 part 5	1.2 N/mm <sup>2</sup>
<b>Modulus of Rupture</b>	EN 310	EN 622 part 5	40 N/mm <sup>2</sup>
<b>Modulus of Elasticity</b>	EN 310	EN 622 part 5	4000 N/mm <sup>2</sup>
<b>Durability</b>	BS 4965	Class D4	-
<b>Thickness tolerance</b>	EN 324-1	EN 622 part 5	+/-0.15 mm
<b>Reaction to fire</b>	EN 13501-1	EN 438:2005	D-s2, d0
<b>Water Vapour Permeability</b>	EN 12572:2001	-	70 wet / 200 dry
<b>Formaldehyde Emission</b>	EN 120	CARB Phase 2	< 1mg per 100g

The performance of the product identified for the type specified is in conformity with the declared performance in the essential characteristics above.

The declaration of performance is issued under the sole responsibility of Norcros Group (Holdings) Ltd T/A Grant Westfield.

Signed for and on behalf of Norcros Group (Holdings) Ltd T/A Grant Westfield by: **John Mortimer**, Managing Director

**SIGNATURE:**

**DATE AND PLACE OF ISSUE:**

Edinburgh on 15 November