



## 0022 HAZARD WARNING TAPE

### DESCRIPTION

A heavy duty PVC colour coding tape, complies with OSHA requirements, very conformable and resistant to abrasion. A high tack rubber adhesive ensures excellent grip to concrete, timber and steel surfaces.

### APPLICATION

Designed for marking of walkways, sports arenas, demarcation of dangerous obstacles etc. Ensure surfaces are clean, dry and free from grease and rust before applying tape. Leave for a minimum of 2 hours before allowing heavy traffic on the surface for best results.

### TECHNICAL SPECIFICATIONS

PROPERTIES	UNIT	AVG. TEST VALUE
Total Thickness	mm	0.15 (6) $\pm$ 10%
Tensile Strength	Kg/1" (lb/1")	7.2 (15.8) min, avg
Elongation	%	200min, avg
<b>Adhesion</b>		
To steel (colour tape)	kg/1" (oz/1")	0.60 (21) min, avg
To steel (transparent tape)	kg/1" (oz/1")	0.50 (17) min, avg
To backing (colour tape)	kg/1" (oz/1")	0.55 (20) min, avg
To backing (transparent tape)	kg/1" (oz/1")	0.45 (16) min, avg
Dielectric breakdown	Kv	7.8 min avg.

Test Method: In accordance with ASTM D-1000

Shelf Life: 12 months when stored at 23deg.C and 65% R.H

The information supplied is accurate to the best of the manufacturers' knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. This document does not form part of any contract with a customer. (14/03/06)

*Specialist converters of technical adhesive tapes and foams*

Tape Range Distributors Limited  
Captain Clarke Road, Broadway Industrial Estate, Hyde, Cheshire, SK14 4QG.  
Tel: +44 (0)161 351 9515 Fax: +44 (0)161 351 9516  
email: [taperange@adhesivetape.net](mailto:taperange@adhesivetape.net)  
vat no: 509 5005 65 reg no: 2578452

