



1316 INTERLEAVED ALUMINIUM FOIL TAPE ACRYLIC ADHESIVE

<u>TECHNICAL DETAILS</u>	<u>TYPICAL VALUE</u>	<u>UNITS</u>
Thickness, foil carrier plus adhesive	0.14	mm
Foil thickness	Level 10	
Adhesive type	Emulsion Acrylic	
Release liner weight	62	g/sq.m
Peel adhesion	400	N/m
Polyester Loop Tack	800	N/m
Release from liner	10	N/m
Tensile strength	5000	N/m
Elongation at break	15	%
Service temperature	-30 to +130	Deg.C
Recommended application temp.	+5 to +25	Dec.C
Moisture vapour permeability	Less than 1	g/m ² , 24h at 40deg.C, 90% RH
Shear adhesion, 1KG @ 23 deg.C	60	Hours
Shelf life	12	Months
Test Methods	3924:1978	

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.

ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR DETERMINING THE SUITABILITY OF THIS PRODUCT FOR THEIR PURPOSES.

Specialist converters of technical adhesive tapes and foams

Tape Range Distributors Limited
Captain Clarke Road, Broadway Industrial Estate, Hyde, Cheshire, SK14 4QG.
Tel: +44 (0)161 351 9515 Fax: +44 (0)161 351 9516
email: taperange@adhesivetape.net
vat no: 509 5005 65 reg no: 2578452



Specialist converters of technical adhesive tapes and foams

Tape Range Distributors Limited
Captain Clarke Road, Broadway Industrial Estate, Hyde, Cheshire, SK14 4QG.
Tel: +44 (0)161 351 9515 Fax: +44 (0)161 351 9516
email: taperange@adhesivetape.net
vat no: 509 5005 65 reg no: 2578452

