Printing date 08/19/2015 Reviewed on 08/19/2015

1 Identification

· Product identifier

· Trade name: Rolmark Solvent

· Article number: RMS-G, RMS-Q, 5A133

• CAS Number: 123-42-2

• **EC number:** 204-626-7

• Index number: 603-016-00-1

· Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Cleaner solvent

Paint

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Marsh Shipping Supply Co.,LLC 926 McDonough Lake Road - Unit E Collinsville, IL 62234

USA

- · Information department: customerservice@msscllc.com
- · Emergency telephone number:

Infotrac: 1-800-535-5053

International; 352-323-3500 (CALL COLLECT)

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

- · Label elements
- · GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms GHS02, GHS07
- · Signal word Warning
- · Hazard statements

Flammable liquid and vapour.

Causes serious eye irritation.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Wear protective gloves / eye protection / face protection.

Wear eye protection / face protection.

Ground/bond container and receiving equipment.

Keep container tightly closed.

(Contd. on page 2)

Printing date 08/19/2015 Reviewed on 08/19/2015

Trade name: Rolmark Solvent

(Contd. of page 1)

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Information pertaining to particular dangers for man and environment:
- · Potential Chronic Health Effects

Prolonged or repeated exposure of vapors, spray, or material may cause diseases of the lungs. Reports have associated repeated overexposure to solvents with brain and nervous system damage. Intentional misuse of this product may be harmful or fatal.

· Target Organs

Overexposure to this material or its components has been suggested as a cause of the following effects in laboratory animals and/or humans, and may aggravate preexisting disorders of these organs in humans: Anemia, Blood disorders, Brain damage, Cardiac function, eye, liver, lung, menstrual and fertility, skin, respiratory, Central Nervous System

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 2Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1 Fire = 2Reactivity = 0

· Other hazards

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description

123-42-2 4-hydroxy-4-methylpentan-2-one

- · Identification number(s)
- · EC number: 204-626-7
- · Index number: 603-016-00-1

4 First-aid measures

- · Description of first aid measures
- · General information:

Take affected persons out into the fresh air.

Involve doctor immediately.

(Contd. on page 3)

Printing date 08/19/2015 Reviewed on 08/19/2015

Trade name: Rolmark Solvent

(Contd. of page 2)

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water for 15 minutes. If irritation exists call physician.
- · After eye contact:

Rinse opened eye for fifteen minutes under running water. If irritation persists, consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Most important symptoms and effects, both acute and delayed

Breathing difficulty

Headache

Thirst

Cramp

Gastric or intestinal disorders

Coughing

Allergic reactions

Nausea

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

Nitrogen oxides (NOx)

Carbon monoxide (CO)

- · Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Wear protective clothing.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Prevent from spreading (e.g. by damming-in or oil barriers).

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Printing date 08/19/2015 Reviewed on 08/19/2015

Trade name: Rolmark Solvent

(Contd. of page 3)

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Handle with care. Avoid jolting, friction and impact.

Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing or moving, observe grounding/grounding of containers and other equipment when handeling.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.
- · Information about storage in one common storage facility:

Do not store together with oxidizing and acidic materials as well as heavy-metal compounds.

Store away from foodstuffs.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from humidity and water.

Protect from exposure to the light.

 \cdot *Specific end use*(s) *No further relevant information available.*

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

123-42-2 4-hydroxy-4-methylpentan-2-one

PEL Long-term value: 240 mg/m³, 50 ppm REL Long-term value: 240 mg/m³, 50 ppm TLV Long-term value: 238 mg/m³, 50 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Pregnant women should strictly avoid inhalation or skin contact.

Do not eat, drink, smoke or sniff while working.

· Breathing equipment:

Use suitable respiratory protective device in case of insufficient ventilation.

Do not breath vapors, spray mists, or sanding dusts. Use air purifying respirators fitted with organic vapor/HEPA cartridges only if air monitoring demonstrates solvent/particulate levels do not exceed the respirator maximum use concentration. Use properly fitted NIOSH approved respirators. Local and general exhaust should minimize any exposure.

(Contd. on page 5)

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/19/2015 Reviewed on 08/19/2015

Trade name: Rolmark Solvent

· Protection of hands:



Protective gloves

· Material of gloves

Nitrile or natural rubber gloves are typically used to protect from minor contact. Butyl type are best for prolonged contact.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Nitrile rubber, NBR

· Eye protection:



Vapor proof safety goggles or full face respirator

· Body protection:

Solvent resistant protective clothing Impervious protective clothing

Tyvek(R) coveralls to protect from light overspray protection or Saranex 23-P(R) for moderate exposure.

9 Physical and chemical properties

| · Information on basic physical and chemical properties | |
|---|----------------------------|
| · General Information | |
| · Appearance: Form: | Fluid |
| rorm: Color: | ruua Clear |
| · Odor: | Cleur Alcohol-like |
| · Odour threshold: | Not determined. |
| · Odour inresnou. | tvoi determined. |
| · pH-value: | Not determined. |
| · Change in condition | |
| Melting point/Melting range: | -47 °C (-53 °F) |
| Boiling point/Boiling range: | 150 °C (302 °F) |
| · Flash point: | 58 °C (136 °F) |
| · Flammability (solid, gaseous): | Not applicable. |
| · Ignition temperature: | 620 °C (1148 °F) |
| Decomposition temperature: | Not determined. |
| · Auto igniting: | Not determined. |
| · Danger of explosion: | Not determined. |
| · Explosion limits: | |
| Lower: | 1.4 Vol % |
| Upper: | 8.1 Vol % |
| · Vapor pressure at 20 °C (68 °F): | 1.1 hPa (1 mm Hg) |
| · Density at 20 °C (68 °F): | 0.93 g/cm³ (7.761 lbs/gal) |
| · Relative density | Not determined. |

(Contd. on page 6)

Printing date 08/19/2015 Reviewed on 08/19/2015

Trade name: Rolmark Solvent

(Contd. of page 5)

Vapour density
Evaporation rate
Not determined.
Not determined.

· Solubility in / Miscibility with

Water: Fully miscible.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:Not determined.Kinematic:Not determined.Organic solvents:100.0 %VOC content:100.0 %

100.0 % 930.0 g/l / 7.76 lb/gl

• *Other information No further relevant information available.*

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions

Forms explosive gas mixture with air.

Reacts with acids, alkalis and oxidizing agents.

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

Nitrogen oxides

Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

123-42-2 4-hydroxy-4-methylpentan-2-one

 Oral
 LD50
 4000 mg/kg (rat)

 Dermal
 LD50
 13630 mg/kg (rab)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization:

Sensitizing effect through inhalation is possible with prolonged exposure.

Sensitizing effect by skin contact is possible with prolonged exposure.

- · Additional toxicological information: Danger through skin absorption.
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

Substance is not listed.

(Contd. on page 7)

Printing date 08/19/2015 Reviewed on 08/19/2015

Trade name: Rolmark Solvent

(Contd. of page 6)

· NTP (National Toxicology Program)

Substance is not listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Assessment by list): slightly hazardous for water This statement was deduced from the properties of the single components.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Hand over to hazardous waste disposers.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

- · UN-Number
- · DOT, ADR, IMDG, IATA UN1148
- · UN proper shipping name
- Diacetone alcohol

 ADR

 1148 Diacetone alcohol

 IMDG, IATA

 DIACETONE ALCOHOL
- · Transport hazard class(es)
- $\cdot DOT$



- · Class 3 Flammable liquids
- · Label
- · Packing group
- \cdot **DOT**

(Contd. on page 8)

Printing date 08/19/2015 Reviewed on 08/19/2015

Trade name: Rolmark Solvent

| | (Contd. of page |
|---|---|
| · Environmental hazards: | |
| Marine pollutant: | No |
| · Special precautions for user | Not applicable. |
| · EMS Number: | F- E , S - D |
| · Transport in bulk according to Annex I. | I of |
| MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| \cdot ADR | |
| · Excepted quantities (EQ) | Code: E1 |
| | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 1000 ml |
| · IMDG | |
| · Excepted quantities (EQ) | Code: E1 |
| | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 1000 ml |
| · UN ''Model Regulation'': | UN1148, Diacetone alcohol |

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · TSCA (Toxic Substances Control Act):

All ingredients are listed or exempt.

123-42-2 4-hydroxy-4-methylpentan-2-one

- · Cancerogenity categories
- · NIOSH (National Institute for Occupational Safety and Health)

123-42-2 4-hydroxy-4-methylpentan-2-one

Guidelines 89-104

- · State regulations
- · New Jersey Right-to-know Trade Secret Registry Number TSRN 67118600000-5004P
- · Massachussetts Right-to-know / Hazardous Substance Codes

123-42-2 4-hydroxy-4-methylpentan-2-one

2,4

· Florida Hazardous / Toxic Substance Lists 123-42-2 4-hydroxy-4-methylpentan-2-one

· Pennsylvania Hazardous Substances

Toxic

123-42-2 4-hydroxy-4-methylpentan-2-one

· Minnesota Right To Know / Hazardous Substances

123-42-2 4-hydroxy-4-methylpentan-2-one

ANO

· Illinois Right To Know

Substance is not listed.

- · GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms GHS02, GHS07
- · Signal word Warning
- · Hazard statements

Flammable liquid and vapour.

Causes serious eye irritation.

(Contd. on page 9)

Printing date 08/19/2015 Reviewed on 08/19/2015

Trade name: Rolmark Solvent

(Contd. of page 8)

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Wear protective gloves / eye protection / face protection.

Wear eye protection / face protection.

Ground/bond container and receiving equipment.

Keep container tightly closed.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Occupational Safety and Health Act (OSHA)

Immediate (acute) health hazard

Delayed (chronic) Health Hazard

- · Water hazard class: Water hazard class 1 (Assessment by list): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

· Recommended restriction of use

FOR PROPERLY TRAINED PROFESSIONAL USERS ONLY. THIS PRODUCT IS NOT FOR GENERAL PUBLIC USE. IT IS INTENDED FOR USE BY QUALIFIED USERS ONLY AFTER HAVING FAMILIARIZED THEMSELVES WITH THE SDS AND UNDERSTAND ALL HAZARDS TO THEMSELVES AND THE ENVIRONMENT, THROUGH A COMPREHENSIVE TRAINING PROGRAM ACCORDING TO 29 CFR.

- · Contact: Compliance Department
- · Date of preparation / last revision 08/19/2015 / -
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2