


Installation guide

1) Secure the mounting tube

Line up the mounting tube and mark where you want to install it. Drill 4 screw holes and the central charge cable hole through the surface. You can use the round metal strengthening plate as a template to mark on the surface where you need to drill. Screw the four double headed screws into the tube all the way, then push the tube and screws into the drill holes. *Remember the power cable has to run through the hole in the middle of the tube, so ensure the middle drill hole is wide enough to pass a USB head through.* Secure the pole from the other side of the surface with the strengthening plate and the bolts provided as per the diagram.



NOTE! If your surface is not between 2.5 and 4.5cm thick or you can't access the other side surface, you need a LocPad screw mount base (ADLOC115W). You can attach the screw mount base to the surface from above, then screw the mounting pole to the base. There is no need to access the surface from behind to install in this case.


2) Attach the enclosure to the tube

Secure the enclosure chassis to the mount tube with the 4 x screws provided. Make sure you install the round metal strengthening plate behind the screws as highlighted in the picture. This is now a good time to ensure your charge cable is fed through the holes and in place



3) Install the fit kit

Install the four corners of the fit kit onto the predefined pegs of the enclosure. Make sure you install the corners the correct orientation, allowing for any indents for power switches / power cables etc.



4) Install the tablet

Connect the charging lead to the tablet and slot your tablet into the 'fit kit'. The tablet should fit perfectly into the fit kit. If it is not, check you have the fit-kit corners the correct way round. If the tablet doesn't fit at all, it's possible you have a fit-kit for another tablet brand. Give us a call.




5) Lay the face plate over the tablet

Peel off the protective covering on the faceplate. Lay the plate on top of the tablet, ensuring it's on the right way round. The camera and home buttons (if selected) should clearly be in the correct place.



6) Install and lock the front metal enclosure plate

There are two hooks on the underside of the metal plate which should line up the appropriate receptacles on the rear part of the enclosure. Slot these in and pivot the rest of the metal plate down onto the enclosure, then press the barrel lock in to lock the face plate in place. Insert the key into the barrel lock and rotate to release the lock and allow the metal plate to be removed again.



Hook the metal front plate here.

