

■ WIRING DIAGRAM

**SS-864**  
**GBW ..**  
Alternating current fan with thermal contact in series.

U1 - brown (BN)    Z2 - orange (OG)  
U2 - blue (BU)    TK - white (WH) or yellow (YE)  
Z1 - black (BK)    PE - yellow/green (YE/GN)

TK in series only with motor < 6A

U1 - blue (BU)  
U2 - black (BK)  
Z - brown (BN)  
PE - yellow/green (YE/GN)

**SS-923**  
**GBW 250/4 and 315/4**  
Single phase A, C, motor with operating capacitor and thermal contact.

TK in series only with motor < 6A

U1 - brown (BN)  
U2 - blue (BU)  
Z1 - black (BK)  
Z2 - orange (OG)  
TK - white (WH) or yellow (YE)  
PE - yellow/green (YE/GN)

**SS-865**  
**GBW 500/4**  
Alternating current fan carried out with thermal contact in order to connect full motor protection units.

**SS-867**  
**GBD ..**  
3~ rotary current, rotation speed switchable, double-rotating, with star-delta connexion 400 V / 400 V and thermal contact.

U1-braun (BN)  
V1-blau (BU)  
W1-schwarz (BK)  
U2-rot (RD)  
V2-grau (GY)  
W2-orange (OG)  
TK-weiß (WH)  
PE-gelb/grün (YE/GN)

U1-braun (BN)  
V1-blau (BU)  
W1-schwarz (BK)  
U2-rot (RD)  
V2-grau (GY)  
W2-orange (OG)  
TK-weiß (WH)  
PE-gelb/grün (YE/GN)

Service und Information