

What's new

Baseline
HomeSiren Jeweller

SmartBracket mounting panel without holding screw

Common battery


Available for all PROs

Superior
HomeSiren S Jeweller

SmartBracket mounting panel with holding screw

Enhanced battery

Available only for accredited partners



Informative alerts


The siren responds to tamper and security system alarms in less than a second. It is loud enough to scare away intruders and attract the attention of neighbours.

The siren LED notifies that the system is armed or disarmed, and a sound signal indicates delay when entering/leaving. These are helpful features for users who control the security system with a keypad or key fob.



Sabotage resistance

- Tamper alarm
- Device authentication to prevent spoofing
- Jamming detection
- Holding screw to secure the device on SmartBracket




Jeweller communication technology

- Up to 2,000 m of radio communication in an open space
- Data is encrypted throughout the transmission process
- Regular polling to display current device statuses




Event notifications

- Alarms of the system's devices
- Security status: armed/disarmed
- Door opening (Chime function)
- After-alarm indication



Flawless autonomy

- Up to 5 years of battery life
- Low battery notifications
- Panasonic pre-installed battery



Quick installation and setup

- Pairing with a hub via QR code
- Remote control and configuration in the app
- Effortless installation and replacement

Compliance with standards EN 50131-4 (Grade 2) PD 6662:2017 INCERT SSF NFA2P Compatibility Hubs Hub Plus, Hub 2 (2G), Hub 2 (4G), Hub 2 Plus, Hub Hybrid (2G), Hub Hybrid (4G) Range extenders ReX, ReX 2	Communication with control panel Jeweller communication technology Frequency bands 868,0 – 868,6 MHz Communication range up to 2,000 m In an open space	Alerts Alarms Acoustic Delay When Entering/Leaving Acoustic Security mode change Acoustic, LED Security mode LED Door opening (Chime function) Acoustic After-alarm indication LED	Features Types of notifications Acoustic, LED Alarm volume from 81 to 105 dB at a distance of 1 m Alarm duration from 3 s to 3 min Piezoelectric buzzer frequency 3.5 ± 0.5 kHz Additional LED connection Available, 3 V==
Power supply Battery 2 × CR123A Battery life up to 5 years	Installation Operating temperature range from –10°C to +40°C Operating humidity up to 75% Protection class IP50	Enclosure Colour white, black Dimensions 75 × 76 × 27 mm Weight 93 g	Complete set HomeSiren S Jeweller SmartBracket panel with holding screw 2 × CR123A batteries (pre-installed) Connector for third-party LED Installation kit Quick start guide



For detailed information, scan the QR code or follow the link:
ajax.systems/support/devices/homesiren-s/



support@ajax.systems



@AjaxSystemsSupport_Bot



ajax.systems