



DEBUS VISTA CANOPY USER GUIDE



SCOPE

This user guide applies to the below Debus VISTA Canopies only:

Vista Canopy – Midnight Black (DEB25004BLK)/ Vista Canopy – Anthracite Grey (DEB25004GRY)/ Vista Canopy – Sunset Orange (DEB25004ORG)/ Vista Canopy – Forest Green (DEB25004GRN)/ Vista Canopy – Ocean Blue (DEB25004BLU)/ Vista Canopy – Chianti Red (DEB25004RED)

Designed to fit vehicles with a connection height of up to 275cm only

CONTENTS

- 1 x VISTA canopy
- 3 x height adjustable aluminium poles
- 10 x adjustable webbing straps
- 7 x steel rock pegs with luminous heads
- 1 x material repair kit
- 1 x Carry bag with handles

BEFORE USE

Select a level, flat surface. Clear away any sharp objects that could damage the fabric.

CONNECTION METHODS

3 methods can be used to connect the Debus VISTA Canopy:

- 1). Twin 4/6mm kador beading connects to awning rails and wind out awnings
- 2). Pole sleeve to be used with a pole and clamp kit (not included) to connect via a roof gutter
- 3). Throw-over straps which are a universal connection for vehicles without an awning rail

QUICK SET UP GUIDE

AWNING RAIL CONNECTION

- Remove the canopy from the carry bag and place flat on the ground with the beading facing the vehicle.
- Slide either the 4 or 6mm beading into your awning rail channel.
- Insert an aluminium pole through the middle eyelet and extend the pole to the approximate height of the vehicle. Buckle in a webbing strap to the female clip at the middle eyelet. Adjust the webbing strap to provide strong tension and peg down in front of the canopy. The canopy should now be able to support itself.
- Insert a second aluminium pole through a corner eyelet and extend the pole to the same height as the middle pole. Adjust the webbing strap to provide strong tension and peg down at a 45 degree angle from the corner pole.
- Insert the third aluminium pole through a corner eyelet and extend to the same height as the middle pole. Adjust the webbing strap to provide strong tension and peg down at a 45 degree angle from the corner pole.
- For additional support; buckle in both webbing straps to the female clips found at the middle of both sides. Adjust the webbing straps to provide strong tension and peg down at the side of the canopy.
- For extra privacy or protection from the wind; remove the middle pole and buckle in the 3 shorter webbing straps found at the front of the canopy and peg down. This set up is shown in FIG 1 below.
- To help rain run off; remove both corner poles and peg down both corner webbing straps at 45 degree angles. This set up is shown in FIG 2 below.

FIG 1



FIG 2



POLE & CLAMP KIT CONNECTION

- Slide the pole through the canopy pole sleeve and position in the roof gutter rail.
- Secure the pole at each end with the pole clamps, angling the clamps upwards so they do not obstruct the van doors.
- Follow the same pitching process as above.

THROW OVER STRAPS CONNECTION

- Buckle in the throw over webbing straps to the female clips on the connection edge of the canopy.
- Extend the length of the straps and throw them over the top of the vehicle.
- Peg each strap down securely slightly wider than the connection edge to improve tension.
- Adjust the straps until the connection edge of the canopy is sitting tightly onto the roof of the vehicle.
- Follow the same pitching process as above.

CARE FOR INSTRUCTIONS

Let the canopy dry completely before placing it back in the bag provided

Clean off any dirt using a sponge and warm water.

Do not use detergent.

Keep away from sparks, flames, and other ignition sources.

SPECIFICATION

Connection height range: Up to 275cm

Kador connection length: 240cm

Canopy dimensions: W x 280cm D x 300cm Adjustable height 80 – 220cm

Material: DebeX Fabric (150D Oxford polyester, 3000mm HH, SPF 50+)

Weight: 2.5kg

WARRANTY

This product carries a 1 year manufacturing defect warranty as standard. Increase your warranty by an extra 1 year by registering the product within 1 month from the date of purchase. Scan the QR code below to complete the warranty form on the Debus website:



E-Mail: contact@debus.co.uk Website: www.debus.uk

Made in China on behalf of Debus Designs Ltd, The Barn, Brookwood Farm, Fenny Bentley, Ashbourne, Derbyshire, UK, DE6 1LE

Version 1 March 2026