


MAKE IT SAFE



Young children can be strangled by loops in pull cords, chains tapes and inner cords that operate the product. To avoid strangulation and entanglement, keep cords out of the reach of young children. Cords may become wrapped around a child's neck. Move beds, cots and furniture away from window covering cords. Do not tie cords together. Make sure cords do not twist and create a loop.


ALUMINIUM VENETIAN BLIND

STEP 1: POSITIONING




Place the blind in the fitting position and tilt forward so that you can see inside the headrail. The brackets must be positioned at least 50mm away from the ladder cord mechanisms.

STEP 2: FITTING THE BRACKETS



Top fixing - For fitting the blind to the upper section of a recess or to the ceiling, the bracket sits directly above the blind. Measure the distance that any handles protrude from the window frame. Mark this measurement on the lintel and use it to position the back of the bracket. Mark the position of the holes and fix the bracket to the lintel with the screws provided.

NB: Rawl plugs will be required if you are fitting the brackets to a concrete or plaster board lintel.



Face fixing - For fitting the blind to a wall or window frame, the bracket sits directly behind the blind. Position the bracket with the swing arm facing directly towards you. Mark the position of the holes and fix the bracket into place using the screws provided.

NB: Rawl plugs will be required if you are fitting the brackets directly to the wall.

STEP 3: FITTING THE BLIND



Push the swing arm clockwise as far as it will go. Place the front edge lip of the headrail onto the lip of the bracket and push the headrail up and back until it is level.

Push the swing arm anti-clockwise until it locks into place, firmly holding the blind headrail.

STEP 3: MAKE IT SAFE



This blind contains two child safety devices; a cord consolidator and an accumulation device. The accumulation device must be securely fixed to the wall or recess adjacent to the blind and out of reach of children. The cord must be secured as shown after each operation of the blind.

- Headrails shall not be installed less than 1.5m from the floor
- The accumulation system shall be installed as close to the headrail as possible and in all cases not less than 1.5m from the floor.