



## Omni-ID<sup>®</sup> Flex 1200

Omni-ID Flex 1200 is a low profile, cost effective RFID tag with superior RF performance. Supplied with an over laminate surface for increased durability, the Flex 1200 is designed specifically as a low cost alternative to hard tags for applications demanding the protection of an over laminate and read ranges up to 12 meters.

### Applications

With its flexibility and consistent RF performance, the Flex 1200 is ideally suited to applications such as:

- ▶ Office equipment
- ▶ Light outdoor use
- ▶ Portals & Returnable Transit Items (RTI)

### Physical Specifications

Coverstock	White synthetic label with transparent over laminate
Size (mm)	75.0 x 25.0 x 2.50
Size (in)	2.95 x 0.98 x 0.10
Weight (g)	1.66



Dimensions stated in mm

### RF Specifications


Protocol	EPC Class 1 Gen2V2
Frequency Range (MHz)	902 - 928 (US), 866 - 868 (EU)
Read Range (Fixed Reader) <sup>1</sup>	Up to 12m (on metal) Up to 8m (off metal)
Read Range (Handheld Reader) <sup>1</sup>	Up to 6m (on metal) Up to 4m (off metal)
Material Compatibility	Optimized for Metal
IC Type (chip)	Monza R6-P
Memory <sup>2</sup>	EPC - 128(96) bits User - 32(64) bits Unique TID - 48 bits

<sup>1</sup> Quoted performance achieved using standard testing methodology on aluminium test plates. Read range is dependent on multiple factors such as; RFID reader transmit power and receiver sensitivity, asset material and environment.


<sup>2</sup> EPC & User memory are reprogrammable, UTID is locked at point of manufacture by IC manufacturer.

### Radiation Patterns

On Metal



Off Metal





## Related Products and Services

- ▶ **Omni-ID IQ 600** - Ultrathin label providing on metal tag functionality, low cost and hassle free deployment.
- ▶ **Omni-ID Flex 600** - Low profile, cost effective tag, ideal for office equipment and portal setups.
- ▶ **Omni-ID Flex 1600** - Low cost alternative to hard tags for applications requiring read ranges up to 16 meters.
- ▶ **Service Bureau** - Omni-ID offers a full service bureau for printing and pre-encoding Omni-ID tags at point of manufacture.



## Environmental Specifications

Storage Temperature	-40 ° to +85 °C
Operation Temperature <sup>1</sup>	-40 ° to +85 °C
Survivability	-40 ° to +85 °C
IP Rating	IP68
Shock and Vibration	MIL STD 810-G
Attachment	Film adhesive (std)
Certifications	RoHS approved CE approved US&Canada (C1D1/D2) certified (option)
	
Warranty	1 year

<sup>1</sup> Excludes adhesive options, consult adhesive data sheets for recommended temperature ratings.

## Ordering Information

Order code	160 - EU, US
Order options	:303 (Customization) :307 (US&Canada (C1D1/D2) certified) :536 (Textured surface adhesive)

Supplied in rolls of 900 tags. Minimum order quantity is 1 roll.