

1. Introduction

RenLease™ QZ 5111 is a wax-based polishable release agent for use with substrates such as modelling and tooling boards, producing a glossy finish.

RenLease™ QX 5111 can be applied with brush or can be sprayed using a range of air-guns.

2. Typical Properties (liquid)

Property	Units	RenLease™ QZ 5111
Flash Point (DIN 51755)	°C	<21
Specific Gravity @25°C	g/cm ³	~0.7
Appearance	-	Low viscosity white liquid

3. Instructions for use as a Mould Release Agent

Wiping/Brushing - Agitate before use; apply two to three thin coats with a lint-free cloth, allowing the coating to dry fully between coats. A sealer (such as RenLease™ QZ 5111) should be used with porous substrates.

Air-gun – Seek advice.

4. Packaging, storage and shelf-life

RenLease™ QZ 5111 is available in a 1 litre pack. Larger sizes can be provided upon request.

RenLease™ QZ 5111 should be stored between 5 and 25°C. Under these conditions, shelf-life in the original, unopened containers is twelve months.

5. Safety Considerations

RenLease™ QZ 5111 is designed for use by professionals only.

The usual safety precaution have to be taken into consideration when dealing with this material.

Detailed information is given in the Material Safety Data Sheet.

If in doubt, contact your Mouldlife representative who can put you in touch with experts who can assist.

Description

Wax-Based Release Agent

Form

Single Part Liquid