PRODUCT DATA SHEET

2 Pack Epoxy Floor Paint

Chemically Curing Gloss Floor Paint



1 OVERVIEW

2 Pack Epoxy Floor Paint is a chemically curing glossy floor coating designed for interior use in high traffic areas. It provides a tough, seamless finish with excellent resistance to most chemicals, solvents and oils, while remaining easy to apply and maintain.

2 APPLICATIONS & USES

- Warehouses, factories, workshops and showrooms
- Interior floors subject to regular foot traffic
- Suitable where vehicle and truck traffic is expected
- Ideal where occasional spillages of chemicals, solvents or oils may occur
- Slip resistance can be enhanced with anti-slip aggregate

3 SURFACE PREPARATION

- Ensure all areas are clean, sound, dry and free from contamination
- Remove oil and grease using a suitable degreasing solution
- Remove laitance by blasting, acid etching or other mechanical methods
- Hard smooth power-floated concrete should be acid etched or mechanically abraded
- On previously painted floors, confirm existing coatings are sound and mechanically abrade all areas where required

4 AVAILABILITY

Available in pack sizes that make 2.5 litres and 5 litres, with further product-page options including 4 x 5 litres, 10 x 5 litres and 20 x 5 litres.

QUICK SPECIFICATION

Coverage	10 m²/litre
Application	Brush / roller / spray
Finish	Gloss
Pot life	8 hours max
Drying time	6 hours
Brand	Trade Paints

★ KEY BENEFITS

- Tough seamless epoxy coating
- Excellent resistance to chemicals, solvents and oils
- Suitable for high traffic interior floors
- Easy to apply and maintain

Trade Paints UK Ltd Unit 5 | Waterglade Industrial Park | Weston Avenue | West Thurrock | Essex | RM20 3FJ

Tel: 0330 122 4771 Email: sales@paints4trade.com Web: www.paints4trade.com

TECHNICAL PRODUCT INFORMATION

PRODUCT INFORMATION (TYPICAL FIGURES)

Product name	2 Pack Epoxy Floor Paint
Brand	Trade Paints
Product type	2 pack chemically curing glossy epoxy floor paint
Recommended use	Interior concrete and previously prepared floor surfaces in high traffic areas
Application methods	Brush, roller or spray
Coverage	Approx. 10 m² per litre
Drying time	Approx. 6 hours
Overcoating time	16–18 hours
Pot life	8 hours maximum
Finish	Gloss
Recommended thinner	2 Pack Epoxy Thinner
MPN / SKU	PT223/25 / PT223

APPLICATION DETAILS

Mix paint well before use and check colour before application.

Minimum application temperature is 10°C.

Components should be mixed together thoroughly before use.

Anti-slip aggregate can be scattered onto the wet first coat, then loose particles brushed away before applying the second coat.

Take care on previously painted floors, as the epoxy may tighten during curing and expose poorly adhered areas in existing coatings.

PRECAUTIONS DURING USE

Area	Guidance
Environment	Interior use only
Substrate	Clean, sound, dry and contaminant free
Traffic exposure	Suitable for regular foot, vehicle and truck traffic

STORAGE

Store in a cool, dry, well-ventilated area. Keep containers tightly sealed when not in use and protect from extremes of temperature. Observe all storage guidance provided in the Safety Data Sheet.

5 SAFETY PRECAUTIONS

- Use only in well-ventilated areas
- Wear suitable protective gloves, clothing and eye / face protection
- Avoid inhalation of vapours and contact with skin or eyes
- Keep containers closed when not in use
- Keep out of reach of children
- Always refer to the current Safety Data Sheet before use

6 LIMITATIONS

The information in this data sheet is based on current product knowledge and practical experience. Actual performance depends on substrate condition, preparation, application method and site conditions, all of which are beyond our control.

This product is intended for interior use only.

Coverage rates are approximate and will vary according to substrate texture, porosity and method of application.

Previously painted floors should be assessed carefully because the curing epoxy may expose weakly adhered areas of existing coatings.

Where compatibility or service conditions are uncertain, a trial area should be carried out before full application.

7 REFERENCES

Product reference	PT223
Issue date	September 2, 2026
Product information source	paints4trade.com - 2 Pack Epoxy Floor Paint

This data sheet supersedes previous 2 Pack Epoxy Floor Paint product information.

TECHNICAL ADVICE

For applications not covered by this data sheet, contact Trade Paints before proceeding.

Always refer to the current Safety Data Sheet before use.