



## SAFETY DATA SHEET

### RENOTUB TOUCH UP ENAMEL PAINT

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No 1907/2006 as amended by Regulations (EU) No. 453/2010 and (EU) 2015/830

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** Renotub Touch Up Enamel Paint  
**Product number** 5060696320504  
**Product SUMI code** F  
**Product SUMI version number** 1.00

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** An air-drying, liquid, solvent-borne paint for DIY and consumer use.  
Touch up enamel paint for bathroom and kitchen appliances and furniture.  
Applied by touch up brush.

##### 1.3. Details of the supplier of the safety data sheet

**Supplier** Renotub  
The Glade Business Centre, Eastern Avenue  
West Thurrock  
Essex  
RM20 3FH  
  
Tel: 0845 838 2225  
sales@renotub.co.uk

**Contact person** Chief Chemist

##### 1.4. Emergency telephone number

**Emergency telephone** Renotub +44 (0)1708 869396 may be contacted (Office hours only)

**National emergency telephone number** Members of the public should contact: 111 in UK, 01 809 2166 in Republic of Ireland

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (SI 2019 No. 720)

**Physical hazards** Flam. Liq. 3 - H226  
**Health hazards** STOT SE 3 - H336  
**Environmental hazards** Not Classified

##### 2.2. Label elements

## RENOTUB TOUCH UP ENAMEL PAINT

### Hazard pictograms



### Signal word

Warning

### Hazard statements

EUH208 Contains COBALT BIS(2-ETHYLHEXANOATE). May produce an allergic reaction.  
H226 Flammable liquid and vapour.  
H336 May cause drowsiness or dizziness.

### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing vapour/ spray.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P284 [In case of inadequate ventilation] wear respiratory protection.  
P312 Call a POISON CENTRE/doctor if you feel unwell.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

### Supplemental label information

EUH066 Repeated exposure may cause skin dryness or cracking.  
EUH210 Safety data sheet available on request.

### Contains

HYDROCARBONS, C9 - C11. n-alkanes, isoalkanes, cyclics, <2% aromatics

### Supplementary precautionary statements

P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P271 Use only outdoors or in a well-ventilated area.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.  
P302/P352 IF ON SKIN: Wash with plenty of soap and water. Do not use solvent thinners or white spirit.  
P501 Dispose of contents/ container in accordance with national regulations.

### Labelling notes

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

HYDROCARBONS, C9 - C11. n-alkanes, isoalkanes,cyclics,<2% aromatics		25-50%
CAS number: 1174522-20-3	EC number: 919-857-5	
<b>Classification</b>		
Flam. Liq. 3 - H226		
Acute Tox. 4 - H332		
STOT SE 3 - H336		
Asp. Tox. 1 - H304		

## RENOTUB TOUCH UP ENAMEL PAINT

<b>XYLENE</b>		<b>1-5%</b>
CAS number: 1330-20-7	EC number: 215-535-7	
<b>Classification</b> Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 3 - H412		
<b>HYDROCARBONS, C10 - C13, n-ALKANES, ISOALKANES, CYCLICS, &lt;2% AROMATICS</b>		<b>1-5%</b>
CAS number: 64742-48-9	EC number: 918-481-9	
<b>Classification</b> Asp. Tox. 1 - H304		
<b>2-ETHYL-HEXANOIC ACID, ZIRCONIUM SALT</b>		<b>0.1 - &lt;1%</b>
CAS number: 22464-99-9	EC number: 245-018-1	
<b>Classification</b> Repr. 2 - H361		
<b>COBALT BIS(2-ETHYLHEXANOATE)</b>		<b>0.1 - &lt;1%</b>
CAS number: 136-52-7	EC number: 205-250-6	
M factor (Acute) = 1		
<b>Classification</b> Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Repr. 1B - H360Fd Aquatic Acute 1 - H400 Aquatic Chronic 3 - H412		

The full text for all hazard statements is displayed in Section 16.

**Composition comments**      The data shown are in accordance with the latest EC Directives.

**Ingredient notes**      Substances presenting a health or environmental hazard within the meaning of Regulation (EC) No. 1272/2008, assigned a Community workplace exposure limit, classified as PBT/vPvB or included in the Candidate List.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

**General information**      In all cases of doubt, or when symptoms persist, seek medical attention.  
 Never give anything by mouth to an unconscious person.  
 If unconscious place in recovery position and seek medical advice.

## RENOTUB TOUCH UP ENAMEL PAINT

<b>Inhalation</b>	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.
<b>Ingestion</b>	If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.
<b>Skin contact</b>	Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
<b>Eye contact</b>	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

### **4.2. Most important symptoms and effects, both acute and delayed**

<b>Inhalation</b>	In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death.
<b>Ingestion</b>	Ingestion may cause nausea, diarrhoea and vomiting.
<b>Skin contact</b>	Prolonged or repeated contact with skin may cause soreness, irritation or dry skin due to a defatting action.
<b>Eye contact</b>	The liquid splashed in the eyes may cause irritation and reversible damage.

### **4.3. Indication of any immediate medical attention and special treatment needed**

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

<b>Suitable extinguishing media</b>	recommended: alcohol resistant foam, CO <sub>2</sub> , powders, water spray/mist
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.

### **5.2. Special hazards arising from the substance or mixture**

<b>Specific hazards</b>	Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.
<b>Hazardous combustion products</b>	Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m <sup>3</sup> . Oxides of carbon. Oxides of nitrogen.

### **5.3. Advice for firefighters**

<b>Protective actions during firefighting</b>	Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.
<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

<b>Personal precautions</b>	Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.
-----------------------------	---

### **6.2. Environmental precautions**

## RENOTUB TOUCH UP ENAMEL PAINT

**Environmental precautions** Do not allow to enter drains or watercourses.  
If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).  
Clean preferably with a detergent - avoid use of solvents.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see section 13.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

**Usage precautions** The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in Section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.  
In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded.  
Electrical equipment should be protected to the appropriate standard.  
Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.  
Operators should wear anti-static footwear clothing, floors should be of conducting type. Isolate from sources of heat, sparks and open flame. Non-sparking tools should be used. Avoid skin and eye contact. Avoid inhalation of dust from sanding.  
Avoid the inhalation of dust, particulates and spray mist arising from the application. Smoking, eating and drinking should be prohibited in application area.  
For personal protection see Section 8.  
Never use pressure to empty: container is not a pressure vessel.  
Always keep in containers of same material as the original one.  
Comply with the health and safety at work laws.  
Do not allow to enter drains or water courses. Wash hands before eating and before leaving the site.  
Remove contaminated clothing and protective equipment before entering eating areas.  
Information on fire and explosion protection.  
Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials, preferably soaked with water, should be stored in purpose-built containers or in metal containers with tight-fitting self-closing lids.  
Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

### 7.2. Conditions for safe storage, including any incompatibilities

## RENOTUB TOUCH UP ENAMEL PAINT

### Storage precautions

Store in accordance with the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). Notes on joint storage.  
 Store away from oxidising agents, from strongly alkaline and strongly acid materials as well of amines, alcohols and water. Additional information on storage conditions  
 Observe label precautions.  
 Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat and direct sunlight.  
 Keep container tightly closed.  
 Keep away from sources of ignition.  
 No smoking.  
 Prevent unauthorised access.  
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

#### Occupational exposure limits

**HYDROCARBONS, C9 - C11. n-alkanes, isoalkanes, cyclics, <2% aromatics**

Long-term exposure limit (8-hour TWA): SUP 150 ppm 1000 mg/m<sup>3</sup>

#### XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m<sup>3</sup>

Sk

#### 2-ETHYL-HEXANOIC ACID, ZIRCONIUM SALT

Long-term exposure limit (8-hour TWA): WEL 5 mg/m<sup>3</sup> as Zr

Short-term exposure limit (15-minute): WEL 10 mg/m<sup>3</sup> as Zr

#### COBALT BIS(2-ETHYLHEXANOATE)

Long-term exposure limit (8-hour TWA): WEL 0.1 mg/m<sup>3</sup>(Sen)  
 as Co

WEL = Workplace Exposure Limit.  
 Sk = Can be absorbed through the skin.

### Ingredient comments

According to EH40 - List of approved workplace exposure limits. For dust the 8 hour TWA's are:-

Respirable dust 4 mg/cu.m (WEL)

Total inhalable dust 10 mg/cu.m (WEL)

### HYDROCARBONS, C9 - C11. n-alkanes, isoalkanes, cyclics, <2% aromatics (CAS: 1174522-20-3)

#### DNEL

Professional - Inhalation; Long term : 871 (8 hr) mg/m<sup>3</sup>

Professional - Dermal; Long term : 77 mg/kg/day

Consumer - Inhalation; Long term : 185 mg/m<sup>3</sup>

Consumer - Dermal; Long term : 46 mg/kg/day

Consumer - Oral; Long term : 46 mg/kg/day

### XYLENE (CAS: 1330-20-7)

### Biological limit values

650 mmol methyl hippuric acid/mol creatinine in urine. Post shift sampling

## RENOTUB TOUCH UP ENAMEL PAINT

<b>DNEL</b>	Industry - Inhalation; Short term systemic effects: 289 mg/m <sup>3</sup>
	Industry - Inhalation; Long term systemic effects: 77 mg/m <sup>3</sup>
	Industry - Inhalation; Short term local effects: 289 mg/m <sup>3</sup>
	Industry - Inhalation; Long term local effects: 77 mg/m <sup>3</sup>
	Industry - Dermal; Short term systemic effects: 174 mg/m <sup>3</sup>
	Consumer - Inhalation; Long term systemic effects: 14.8 mg/m <sup>3</sup>
	Consumer - Inhalation; Short term local effects: 174 mg/m <sup>3</sup>
	Consumer - Inhalation; Short term systemic effects: 174 mg/m <sup>3</sup>
	Consumer - Dermal; Long term systemic effects: 108 mg/kg/day
	Consumer - Oral; Long term systemic effects: 1.6 mg/kg/day

<b>PNEC</b>	- Fresh water; 0.327 mg/l
	- marine water; 0.327 mg/l
	- Intermittent release; 0.327 mg/l
	- Sediment (Freshwater); 12.46 mg/kg
	- Sediment (Marinewater); 12.46 mg/kg
	- Soil; 2.31 mg/kg
	- STP; 6.58 mg/l

### HYDROCARBONS, C10 - C13, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

<b>DNEL</b>	No data available.
-------------	--------------------

<b>PNEC</b>	No data available.
-------------	--------------------

### 2-ETHYL-HEXANOIC ACID, ZIRCONIUM SALT (CAS: 22464-99-9)

<b>DNEL</b>	Industry - Inhalation; Long term systemic effects: 5 mg/m <sup>3</sup>
	Industry - Dermal; Long term systemic effects: 15.75 mg/kg/day
	Consumer - Inhalation; Long term systemic effects: 2.5 mg/m <sup>3</sup>
	Consumer - Dermal; Long term systemic effects: 7.9 mg/kg/day
	Consumer - Oral; Long term systemic effects: 7.9 mg/kg/day

<b>PNEC</b>	- Fresh water; 0.36 mg/l
	- marine water; 0.036 mg/l
	- Intermittent release; 0.493 mg/l
	- STP; 71.7 mg/l
	- Sediment (Freshwater); 6.37 mg/kg
	- Sediment (Marinewater); 0.637 mg/kg
	- Soil; 1.06 mg/kg

### COBALT BIS(2-ETHYLHEXANOATE) (CAS: 136-52-7)

<b>DNEL</b>	Workers - Inhalation; Long term local effects: 235.1 µg/m <sup>3</sup>
	General population - Inhalation; Long term local effects: 37 µg/m <sup>3</sup>
	General population - Oral; Long term systemic effects: 27.6 µg/kg bw/day

<b>PNEC</b>	Fresh water; 0.00149 mg/l
	marine water; 0.0069 mg/l
	STP; 1.08 mg/l
	Sediment (Freshwater); 27.8 mg/kg, dry weight (dw)
	Sediment (Marinewater); 17.8 mg/l, dry weight (dw)
	Soil; 123.1 mg/kg, dry weight (dw)

## 8.2. Exposure controls

## RENOTUB TOUCH UP ENAMEL PAINT

### Protective equipment



### Safe use of mixture

This Safety Data Sheet should be read in conjunction with the Safe Use of Mixture (SUMI) report referred to in Section 1. The SUMI provides information collated from exposure scenarios of substances relevant to this product and is provided as part of our obligations under REACH Regulations.

### Two-pack product protection

Not applicable

### Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of solvent vapour below the OEL, suitable respiratory protection must be worn. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used. See Respiratory Equipment below.

### Personal protection

Requirements for personal protection can only be determined by performing a risk assessment on a case-by-case basis prior to use. This risk assessment should be reviewed regularly.

### Eye/face protection

Use safety eyewear, manufactured/tested to EN 166, and designed to protect against splash of liquids.

### Hand protection

Wear chemical resistant gloves classified under "Standard EN374: Protective gloves against chemicals and micro-organisms" made from PE, PVA or Viton gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

### Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact. Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

### Hygiene measures

Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. Do not eat, drink or smoke when using this product.



## RENOTUB TOUCH UP ENAMEL PAINT

### Respiratory protection

Selection of any respiratory protective equipment should ensure that it is adequate to reduce exposure to protect the worker's health and is suitable for the wearer, task and environment, including consideration of the facial features of the wearer.

\* Spraying should be undertaken outdoor or in a vented booth. As a minimum, workers should wear a full face respirator to EN136, fitted with a filter suitable for both particulates and vapours, with an assigned protection factor 20 (e.g. A2/P3). A powered full face respirator with combined filter A2/P3 (APF 40) or compressed air breathing apparatus should be worn if used continuously more than 1 hour. Respirators must be worn by anyone in the booth or room during spraying, gun cleaning (spray-to-dry) and throughout the clearance time, until such time as the particulates and solvent vapour concentration have fallen below the appropriate occupational exposure limits.

\* Brush or roller applications should be carried out outdoor or in good ventilation areas with 10 to 15 air changes per hour or more. As a minimum, a half face mask respirator with combined filter A2/P3 (APF 20) should be worn. A powered full face respirator with combined filter A2/P3 (APF 40) should be used, if used for more than 1 hour continuously as half face powered respirator are not recommended.

\* For other operations: If workers could be exposed to concentration above the exposure limit or where ventilation is poor, they must use a respirator, fitted with a filter suitable for both particulates and vapours, with an assigned protection factor of at least 10 (e.g. A2/P3).

\* Enclosed spaces with little or no ventilation: compressed air breathing apparatus should always be worn.

\* Respiratory protection should not be removed until the particulate and solvent vapour concentrations have fallen below the occupational exposure limits or the operator has entered a clean air area.

\* Fit testing and regular servicing is recommended for all respiratory protective equipment.

\* The use of HSE website is strongly recommended in selecting the most appropriate RPE <http://www.healthyworkinglives.com/rpe-selector>

### Environmental exposure controls

Do not allow to enter drains or water courses.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid.
Colour	Various
Odour	Naphthenic
Odour threshold	Not determined.
pH	Not determined.
Melting point	<-20°C
Initial boiling point and range	145 - 200°C @ 760 mm Hg
Flash point	38 - 40°C Setaflash closed cup.
Evaporation rate	0.11
Flammability (solid, gas)	Material is not a solid or gas
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 0.6 % Upper flammable/explosive limit: 8 %
Vapour pressure	0.21 kPa @ °C
Vapour density	Heavier than air

## RENOTUB TOUCH UP ENAMEL PAINT

<b>Relative density</b>	0.9 - 1.2 @ 20°C
<b>Solubility(ies)</b>	Immiscible with water.
<b>Partition coefficient</b>	Not determined.
<b>Auto-ignition temperature</b>	230 - 270°C
<b>Decomposition Temperature</b>	Not determined.
<b>Viscosity</b>	350 - 450 mPa•s, Rotothinner @ 20°C
<b>Explosive properties</b>	The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
<b>Oxidising properties</b>	The product is not expected to be oxidising

### 9.2. Other information

<b>Volatile organic compound</b>	This product contains a maximum VOC content of 420 g/litre.
----------------------------------	---

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

<b>Reactivity</b>	Stable under recommended storage and handling conditions (see section 7). When exposed to high temperatures may produce hazardous decomposition products.
-------------------	--

### 10.2. Chemical stability

<b>Stability</b>	Stable under recommended storage and handling conditions (see section 7).
------------------	---

### 10.3. Possibility of hazardous reactions

<b>Possibility of hazardous reactions</b>	Keep away from oxidising agents, strongly alkaline and strongly acid materials
---	--

### 10.4. Conditions to avoid

<b>Conditions to avoid</b>	Avoid heat, flames and other sources of ignition. When exposed to high temperatures may produce hazardous decomposition products.
----------------------------	---

### 10.5. Incompatible materials

<b>Materials to avoid</b>	Keep away from oxidising agents, strongly alkaline and strongly acid materials
---------------------------	--

### 10.6. Hazardous decomposition products

<b>Hazardous decomposition products</b>	such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.
---	---

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - dermal

<b>ATE dermal (mg/kg)</b>	65,232.85
---------------------------	-----------

#### Acute toxicity - inhalation

<b>ATE inhalation (gases ppm)</b>	397,327.35
-----------------------------------	------------

<b>ATE inhalation (vapours mg/l)</b>	66.9
--------------------------------------	------

<b>ATE inhalation (dusts/mists mg/l)</b>	593.03
--	--------

#### Skin corrosion/irritation

<b>Skin corrosion/irritation</b>	Repeated exposure may cause skin dryness or cracking.
----------------------------------	---

## RENOTUB TOUCH UP ENAMEL PAINT

### Serious eye damage/irritation

**Serious eye damage/irritation** Based on available data the classification criteria are not met.

### Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

### Skin sensitisation

**Skin sensitisation** Contains COBALT BIS(2-ETHYLHEXANOATE). May produce an allergic reaction.

### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

**Genotoxicity - in vivo** Based on available data the classification criteria are not met.

### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

### Reproductive toxicity

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

**Reproductive toxicity - development** Based on available data the classification criteria are not met.

### Specific target organ toxicity - single exposure

**STOT - single exposure** Vapours may cause drowsiness and dizziness.

**Target organs** Central nervous system

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Based on available data the classification criteria are not met.

### Aspiration hazard

**Aspiration hazard** Based on available data the classification criteria are not met.

### General information

There are no data available on the mixture itself. The mixture has been assessed following the method according to the "Classification, labelling and packaging of substances and mixtures" EC 1272/2008 and ensuing amendments and classified for toxicological hazards accordingly. See sections 2 and 3 for details.

### Inhalation

Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

### Ingestion

Ingestion may cause nausea, diarrhoea and vomiting.

### Skin contact

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals after repeated contact.

### Eye contact

Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain. The liquid splashed in the eyes may cause irritation and reversible damage.

### Route of exposure

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### Medical symptoms

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.  
Solvents may cause some of the above effects by absorption through the skin.

## RENOTUB TOUCH UP ENAMEL PAINT

**Medical considerations** This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### Toxicological information on ingredients.

#### HYDROCARBONS, C9 - C11. n-alkanes, isoalkanes, cyclics, <2% aromatics

##### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> mg/kg) 5,000.0

Species Rat

ATE oral (mg/kg) 5,000.0

##### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> mg/kg) 5,000.0

Species Rabbit

ATE dermal (mg/kg) 5,000.0

##### Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 13.1

Species Rat

ATE inhalation (vapours mg/l) 13.1

##### Skin corrosion/irritation

Animal data Prolonged skin contact may defat the skin and produce dermatitis.

##### Serious eye damage/irritation

Serious eye damage/irritation Slightly irritating.

##### Respiratory sensitisation

Respiratory sensitisation No information available.

##### Skin sensitisation

Skin sensitisation Not sensitising.

##### Germ cell mutagenicity

Genotoxicity - in vitro Ames test: Negative. Chromosome aberration: Negative. Gene mutation: Negative.

Genotoxicity - in vivo Micronucleus test: Negative.

##### Carcinogenicity

Carcinogenicity Not expected to be carcinogenic.

##### Reproductive toxicity

Reproductive toxicity - fertility By analogy with comparable product: Animal testing did not show any effects on fertility Parental Toxicity - LOAEL 1500 mg/kg/day, , Fertility - NOAEL 1500 mg/kg/day, Oral, Rat

## RENOTUB TOUCH UP ENAMEL PAINT

**Reproductive toxicity - development** Developmental toxicity: - NOAEL: 5.22 mg/l, Maternal toxicity: - NOAEL:  $\geq 5.22$  mg/l, Inhalation, Rat

### Specific target organ toxicity - single exposure

**STOT - single exposure** Central nervous system depression including narcotic effects such as drowsiness, narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.

**Target organs** Central nervous system Kidneys

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** By analogy with comparable product: Based on available data, the classification criteria are not met. NOAEL  $\geq 11.6$  mg/l, Inhalation, Rat

### Aspiration hazard

**Aspiration hazard** If swallowed accidentally, the product may enter the lungs due to its low viscosity and lead to the rapid development of very serious inhalation pulmonary lesions (medical survey during 48 hours)

**Inhalation** Vapours have a narcotic effect. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting.

**Ingestion** If swallowed accidentally, the product may enter the lungs due to its low viscosity and lead to the rapid development of very serious inhalation pulmonary lesions (medical survey during 48 hours)

**Skin contact** Prolonged contact may cause dryness of the skin.

**Eye contact** May cause temporary eye irritation.

## XYLENE

### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 3,523.0

**Species** Rat

**ATE oral (mg/kg)** 3,523.0

### Acute toxicity - dermal

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 4,200.0

**Species** Rabbit

**ATE dermal (mg/kg)** 1,100.0

### Acute toxicity - inhalation

**Acute toxicity inhalation (LC<sub>50</sub> gases ppmV)** 6,700.0

**Species** Rat

**Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)** 27.6

**Species** Rat

## RENOTUB TOUCH UP ENAMEL PAINT

<b>Acute toxicity inhalation (LC<sub>50</sub> dust/mist mg/l)</b>	10.0
<b>Species</b>	Rat
<b>ATE inhalation (gases ppm)</b>	6,700.0
<b>ATE inhalation (vapours mg/l)</b>	27.6
<b>ATE inhalation (dusts/mists mg/l)</b>	10.0
<b><u>Skin corrosion/irritation</u></b>	
<b>Animal data</b>	Dose: 24 and, 72 hours, Rabbit Irritating to skin.
<b><u>Serious eye damage/irritation</u></b>	
<b>Serious eye damage/irritation</b>	Causes serious eye irritation.
<b><u>Respiratory sensitisation</u></b>	
<b>Respiratory sensitisation</b>	Not sensitising
<b><u>Skin sensitisation</u></b>	
<b>Skin sensitisation</b>	- Mouse: Not sensitising.
<b><u>Germ cell mutagenicity</u></b>	
<b>Genotoxicity - in vitro</b>	Chromosome aberration: Negative. Ames test: Negative. Gene mutation: Negative.
<b>Genotoxicity - in vivo</b>	Dominant lethal assay, intraperitoneal: Negative.
<b><u>Carcinogenicity</u></b>	
<b>Carcinogenicity</b>	NOAEL 500 mg/kg, Oral, Rat, male/female Did not show carcinogenic effects in animal experiments.
<b>IARC carcinogenicity</b>	IARC Group 3 Not classifiable as to its carcinogenicity to humans.
<b><u>Reproductive toxicity</u></b>	
<b>Reproductive toxicity - fertility</b>	One-generation study - NOAEL ≥500 ppm, Inhalation, Rat, male/female P Two-generation study - NOAEL 500 ppm, Inhalation, Rat, male/female P Two-generation study - NOAEL >500 ppm, Inhalation, male/female F1 Two-generation study - NOAEL >500 ppm, Inhalation, Rat, male/female F2 This substance has no evidence of toxicity to reproduction.
<b>Reproductive toxicity - development</b>	Maternal toxicity: - NOAEL: 500 ppm, Inhalation, Rat, female
<b><u>Specific target organ toxicity - single exposure</u></b>	
<b>STOT - single exposure</b>	May cause respiratory irritation.
<b>Target organs</b>	Central nervous system Liver Kidneys
<b><u>Specific target organ toxicity - repeated exposure</u></b>	
<b>STOT - repeated exposure</b>	NOAEL 150 mg/kg, (3 months), Oral, Rat NOAEL >3.5 mg/l, (3 months), Inhalation, Rat, Dog
<b>Target organs</b>	Kidneys Liver

## RENOTUB TOUCH UP ENAMEL PAINT

### Aspiration hazard

**Aspiration hazard** Aspiration hazard - Category 1 If swallowed accidentally, the product may enter the lungs due to its low viscosity and lead to the rapid development of very serious inhalation pulmonary lesions (medical survey during 48 hours)

### HYDROCARBONS, C10 - C13, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

#### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 15,001.0

**Species** Rat

**ATE oral (mg/kg)** 15,001.0

#### Aspiration hazard

**Aspiration hazard** Aspiration hazard - Category 1 May be fatal if swallowed and enters airways.

**Ingestion** Harmful if swallowed. Irritating to mouth, throat and stomach.

**Skin contact** The product is irritating to eyes and skin. May cause an allergic skin reaction.

**Eye contact** Causes serious eye irritation.

### 2-ETHYL-HEXANOIC ACID, ZIRCONIUM SALT

#### Skin corrosion/irritation

**Animal data** Erythema/eschar score: No erythema (0). (rabbit) Oedema score: No oedema (0). (rabbit) Not irritating.

#### Serious eye damage/irritation

**Serious eye damage/irritation** Not irritating. (rabbit)

#### Respiratory sensitisation

**Respiratory sensitisation** No specific test data are available.

#### Skin sensitisation

**Skin sensitisation** Not sensitising. Guinea pig maximisation test Read-across data.

#### Germ cell mutagenicity

**Genotoxicity - in vitro** Chromosome aberration: Negative. Read-across data.

**Genotoxicity - in vivo** Micronucleus test: Negative. Read-across data.

#### Reproductive toxicity

**Reproductive toxicity - fertility** One-generation study - NOEL 300 mg/kg/day, Oral, Rat P Read across data

**Reproductive toxicity - development** Developmental toxicity: - NOEL: 100 mg/kg/day, Oral, Rat Read-across data.  
Maternal toxicity: - NOEL: 250 mg/kg/day, Oral, Rat Read-across data.

#### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** NOEL 3150 - 7080 mg/kg/day, Oral, Rat Read-across data.

### COBALT BIS(2-ETHYLHEXANOATE)

## RENOTUB TOUCH UP ENAMEL PAINT

### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> 3,129.0  
mg/kg)

Species Rat

### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> 2,001.0  
mg/kg)

Species Rat

## SECTION 12: Ecological information

**Ecotoxicity** There are no data available on the mixture itself. The mixture has been assessed following the method according to the "Classification, labelling and packaging of substances and mixtures" EC1272/2008 and ensuing amendments and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details. Do not allow to enter drains or water courses.

### 12.1. Toxicity

**Toxicity** There is no toxicity data for the mixture itself.

### Ecological information on ingredients.

#### HYDROCARBONS, C9 - C11. n-alkanes, isoalkanes, cyclics, <2% aromatics

##### Acute aquatic toxicity

Acute toxicity - fish LC<sub>50</sub>, 96 hours: > 1000 mg/l, Oncorhynchus mykiss (Rainbow trout)  
OECD

Acute toxicity - aquatic invertebrates EC<sub>50</sub>, 48 hours: > 1000 mg/l, Daphnia magna  
OECD

Acute toxicity - aquatic plants IC<sub>50</sub>, 72 hours: >1000 mg/l, Pseudokirchneriella subcapitata

Acute toxicity - microorganisms EC<sub>50</sub>, 48 hours: 43.98 mg/l,

##### Chronic aquatic toxicity

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 0.23 mg/l, Daphnia magna

#### XYLENE

##### Acute aquatic toxicity

Acute toxicity - fish LC<sub>50</sub>, 96 hours: 2.6 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EC<sub>50</sub>, 24 hours: 1 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC<sub>50</sub>, 72 hours: 2.2 mg/l, Freshwater algae, Pseudokirchneriella subcapitata  
NOEC, 72 hours: 0.44 mg/l, Pseudokirchneriella subcapitata

Acute toxicity - microorganisms EC<sub>50</sub>, 24 hours: 96 mg/l, Bacteria

##### Chronic aquatic toxicity



## RENOTUB TOUCH UP ENAMEL PAINT

**Chronic toxicity - fish early life stage** NOEC, 56 days: > 1.3 mg/l, Oncorhynchus mykiss (Rainbow trout)

**Chronic toxicity - aquatic invertebrates** NOEC, 21 days: 1.57 mg/l, Daphnia magna

### HYDROCARBONS, C10 - C13, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

#### Acute aquatic toxicity

**Acute toxicity - fish** LL0, 96 hours: 1000 mg/l, Oncorhynchus mykiss (Rainbow trout)

**Acute toxicity - aquatic invertebrates** LL0, 48 hours: 1000 mg/l, Daphnia magna

**Acute toxicity - aquatic plants** NOELR, 72 hours: 1000 mg/l, Pseudokirchneriella subcapitata  
QSAR prediction

**Acute toxicity - microorganisms** EL50, 48 hours: >1000 mg/l, Tetrahymena pyriformis

#### Chronic aquatic toxicity

**Chronic toxicity - fish early life stage** NOELR, 28 days: 0.1 mg/l, Onchorhynchus mykiss (Rainbow trout)

**Chronic toxicity - aquatic invertebrates** NOELR, 21 days: 0.18 mg/l, Daphnia magna

### 2-ETHYL-HEXANOIC ACID, ZIRCONIUM SALT

#### Acute aquatic toxicity

**Acute toxicity - fish** NOELR, 96 hours: >=100 mg/l, Brachydanio rerio (Zebra Fish)

**Acute toxicity - aquatic invertebrates** NOEC, 48 hours: 0.17 mg/l, Daphnia magna

**Acute toxicity - aquatic plants** EC<sub>50</sub>, 72 hours: 49.3 mg/l, Desmodesmus subspicatus

**Acute toxicity - microorganisms** EC<sub>50</sub>, 17 hours: 112.1 mg/l, Pseudomonas putida

### COBALT BIS(2-ETHYLHEXANOATE)

#### Acute aquatic toxicity

**LE(C)<sub>50</sub>** 0.1 < L(E)C<sub>50</sub> ≤ 1

**M factor (Acute)** 1

**Acute toxicity - fish** , : 1.5 mg/l,

## 12.2. Persistence and degradability

**Persistence and degradability** There is no data for the mixture itself.

### Ecological information on ingredients.

#### HYDROCARBONS, C9 - C11. n-alkanes, isoalkanes, cyclics, <2% aromatics

**Persistence and degradability** 28 days - 80% readily biodegradable - OECD 301F

## RENOTUB TOUCH UP ENAMEL PAINT

### XYLENE

<b>Persistence and degradability</b>	Readily biodegradable
<b>Biodegradation</b>	- Degradation % >60: 28 days Readily biodegradable

### HYDROCARBONS, C10 - C13, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

<b>Phototransformation</b>	Not expected to be significant
<b>Biodegradation</b>	Water - Degradation 80%: 28 days Readily biodegradable

### 2-ETHYL-HEXANOIC ACID, ZIRCONIUM SALT

<b>Phototransformation</b>	Water - DT <sub>50</sub> : 47.1 hours Read-across data.
<b>Stability (hydrolysis)</b>	Not hydrolysable Read-across data.
<b>Biodegradation</b>	Water - Degradation % 46.54: 10 days Water - Degradation % 73.82: 28 days

### 12.3. Bioaccumulative potential

<b>Bioaccumulative potential</b>	There is no data for the mixture itself.
<b>Partition coefficient</b>	Not determined.

### Ecological information on ingredients.

### HYDROCARBONS, C9 - C11. n-alkanes, isoalkanes, cyclics, <2% aromatics

<b>Bioaccumulative potential</b>	May accumulate in soil and water systems.
<b>Partition coefficient</b>	log Pow: 5 - 6.7

### XYLENE

<b>Bioaccumulative potential</b>	Not expected to bioaccumulate. BCF: 25.9,
<b>Partition coefficient</b>	log Pow: 3.15

### HYDROCARBONS, C10 - C13, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

<b>Bioaccumulative potential</b>	No information available.
<b>Partition coefficient</b>	No information available.

### 2-ETHYL-HEXANOIC ACID, ZIRCONIUM SALT

<b>Bioaccumulative potential</b>	log Pow: 2.96, Read-across data.
----------------------------------	----------------------------------

### 12.4. Mobility in soil

<b>Mobility</b>	The product is immiscible with water and will spread on the water surface. The product contains organic solvents which will evaporate easily from all surfaces.
-----------------	---

### Ecological information on ingredients.

## RENOTUB TOUCH UP ENAMEL PAINT

### HYDROCARBONS, C9 - C11. n-alkanes, isoalkanes, cyclics, <2% aromatics

<b>Mobility</b>	The product contains organic solvents which will evaporate easily from all surfaces. In soil the product has only slight mobility and will partially evaporate. The product has poor water-solubility.
<b>Surface tension</b>	0.0237 mN/m @ 25°C

### XYLENE

<b>Mobility</b>	The product contains volatile solvents which are immiscible with water and will evaporate into the atmosphere. In soil the product has only slight mobility and will partially evaporate.
-----------------	---

### HYDROCARBONS, C10 - C13, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

<b>Mobility</b>	The product contains volatile solvents which are immiscible with water and will evaporate into the atmosphere. Not expected to partition to sediment and wastewater solids.
-----------------	---

### 2-ETHYL-HEXANOIC ACID, ZIRCONIUM SALT

<b>Henry's law constant</b>	0.294 Pa m <sup>3</sup> /mol @ 25°C Read-across data.
-----------------------------	---

### 12.5. Results of PBT and vPvB assessment

<b>Results of PBT and vPvB assessment</b>	This product does not contain any substances classified as PBT or vPvB.
---	---

### 12.6. Other adverse effects

<b>Other adverse effects</b>	Not determined.
------------------------------	-----------------

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

<b>General information</b>	Do not allow to enter drains or water courses or dispose of where ground or surface waters may be affected. Waste and emptied containers should be classified in accordance with "The Environment Protection (Duty of Care) Regulations" (in England, Scotland, Wales or The Controlled Waste (Duty of Care) Regulations in Northern Ireland).
<b>Waste class</b>	The European List of Wastes classification of this product, when disposed of as waste is: Waste Code: Name of Waste (according to Decision 2000/532/EC): 08 01 11 Waste paint and varnish containing organic solvents or other dangerous substances If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information contact your local waste authority. Using the information provided in this safety data sheet, advice should be obtained from the relevant environment agency whether the Hazardous Waste Regulations apply. Empty containers must be scrapped or reconditioned. Dispose of empty containers contaminated by the product in accordance with local or national legal provisions.

### **Additional information**

## **SECTION 14: Transport information**

<b>General</b>	This section contains basic classification information; specific information is not provided for all transport modes if not relevant for the product as supplied. Relevant modal regulations should be consulted if the product is transported onwards.
----------------	---

## RENOTUB TOUCH UP ENAMEL PAINT

**Road transport notes**

VISCOUS FLAMMABLE LIQUID DEROGATION

In pack sizes less than 450 litres, under the terms of 2.2.3.1.5, this product is not subject to the provisions of ADR.

**Sea transport notes**

VISCOUS FLAMMABLE LIQUID DEROGATION:

In pack sizes up to and including 30 litres, under the terms of 2.3.2.5, this product is not subject to the packaging, labelling and marking requirements of the IMDG Code, but both full documentation and placarding of cargo transport units is still required.

**Air transport notes**

VISCOUS FLAMMABLE LIQUID DEROGATION:

The "viscosity exemption" provision does not apply to air transport.

**14.1. UN number**

UN 1263

**14.2. UN proper shipping name**

PAINT

**14.3. Transport hazard class(es)**

3

ADR/RID label

3

**Transport labels****14.4. Packing group**

PG III

**14.5. Environmental hazards**

Environmentally hazardous substance/marine pollutant

No.

**14.6. Special precautions for user**

Transport within the user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of accident or spillage.

EmS

F-E, S-E

Tunnel restriction code

(D/E)

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**

Transport in bulk according to Not relevant.

Annex II of MARPOL 73/78  
and the IBC Code

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

# RENOTUB TOUCH UP ENAMEL PAINT

## EU legislation

Waste Framework Directive (Directive 2008/98/EC on waste) and amendments

Directive 2004/42/EC on Volatile Organic Compounds (VOC)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

**Paints Directive 2004/42/EC** 2004/42/IB(d)(420)420

## 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## SECTION 16: Other information

<b>General information</b>	The product should not be used for purposes other than those shown in Section 1.
<b>Key literature references and sources for data</b>	Raw material supplier's Safety Data Sheets. Reference to ECHA Registered Substance dossiers.
<b>Classification procedures according to SI 2019 No. 720</b>	Unless indicated elsewhere in this safety data sheet, the classification of this mixture has been determined using a combination of test data, bridging principles and calculation.
<b>Legal obligations</b>	
<b>Revision comments</b>	Formulation adjusted to meet the requirement of the 15th ATP
<b>Issued by</b>	Chief Chemist
<b>Revision date</b>	11/01/2022
<b>Revision</b>	CLP 1.04
<b>Supersedes date</b>	18/11/2020
<b>SDS number</b>	10517
<b>Hazard statements in full</b>	<p>H226 Flammable liquid and vapour.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>H312 Harmful in contact with skin.</p> <p>H315 Causes skin irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H319 Causes serious eye irritation.</p> <p>H332 Harmful if inhaled.</p> <p>H335 May cause respiratory irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H360Fd May damage fertility. Suspected of damaging the unborn child.</p> <p>H361 Suspected of damaging fertility or the unborn child.</p> <p>H373 May cause damage to organs through prolonged or repeated exposure.</p> <p>H400 Very toxic to aquatic life.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p> <p>EUH208 Contains COBALT BIS(2-ETHYLHEXANOATE). May produce an allergic reaction.</p>

The information of this SDS is based on the present state of our knowledge and on current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not to be used for purposes other than those shown in section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information in this safety data sheet does not constitute the user's own assessment of workplace risks as required by other health and safety legislation.