

PRODUCT DATA SHEET

Rust Converter

Water-Based Metal Rust Converter

1 OVERVIEW

Our Water-Based Metal Rust Converter is a premium, multi-functional rust treatment that transforms rusted ferrous metal into a stable, paint-ready surface in a single step. Low odour and easy to clean up, it provides long-lasting rust inhibition for interior and exterior applications and is suitable for DIY projects and professional restoration work.

2 APPLICATIONS & USES

- Cars, machinery, gates and fences
- Rusty iron, steel and other ferrous metals
- DIY projects and professional restorations
- Brush, roller or spray application
- Interior and exterior metal applications

3 KEY BENEFITS

- Neutralises rust into a stable, protective surface
- Water-based, low odour and easy clean-up
- Long-lasting rust inhibitor
- Paint-ready after treatment and drying
- Suitable as rust proofer, repair paint or anti-rust primer



QUICK SPECIFICATION

Coverage	8 m ² /litre
Application	Brush / roller / spray
Finish	Satin
Drying time	60 minutes
Overcoating	4-6 hours
Brand	Trade Paints

★ KEY BENEFITS

- Converts rust for painting
- Water-based & low odour
- Long-lasting rust inhibition
- Interior & exterior use



TECHNICAL PRODUCT INFORMATION

PRODUCT INFORMATION (TYPICAL FIGURES)

Product name	Rust Converter
Brand	Trade Paints
Product type	Water-based multi-functional rust converter and treatment
Recommended substrates	Cars, machinery, gates, fences, rusty iron, steel and other ferrous metal surfaces
Application methods	Brush, roller or spray
Coverage	Approx. 8 m ² per litre
Drying time	Approx. 60 minutes
Overcoating time	Approx. 4-6 hours
Finish	Satin
Recommended thinner / cleaner	Water
Available sizes	1 litre and 2.5 litre
MPN / SKU	Rust/1

SURFACE PREPARATION

Ensure the surface is clean, dry and free from loose rust, grease and contamination.

Remove loose or flaking rust before application and ensure the metal is sound.

For unfamiliar substrates or non-standard conditions, obtain technical advice before full application.

APPLICATION GUIDANCE

Apply by brush, roller or suitable spray equipment.

Typical coverage is approximately 8 m² per litre.

The listed finish is satin.

Touch dry in approximately 60 minutes; overcoat after 4-6 hours.

Clean brushes, rollers and spray equipment with water after use.

STORAGE

Store in a cool, dry place, protect from frost and keep containers tightly closed when not in use.



PRODUCT DATA SHEET

4 SAFETY PRECAUTIONS

- Use in well-ventilated areas
- Wear protective gloves and eye protection
- Avoid inhalation and contact with skin or eyes
- Clean tools with water after use
- Keep out of reach of children
- Refer to the current product label and Safety Data Sheet before use

5 LIMITATIONS

This standardised sheet is compiled from the current Paints4Trade product listing for Rust Converter. The live product page, product label and Safety Data Sheet remain authoritative.

Coverage and drying times are typical values and may vary with substrate condition, temperature, humidity and application method. The product page states a full cure of approximately 24 hours for maximum protection.

Always test suitability on the intended substrate and obtain technical advice where project conditions are unusual or critical.

For unfamiliar substrates, non-standard exposures or safety-critical applications, obtain technical advice before use.

6 REFERENCES & DOCUMENT CONTROL

Product	Rust Converter
Document reference	Rust/1
Issue date	September 3, 2026
Primary source	https://paints4trade.com/rust-converter-266116-p.asp
Product data basis	Current linked Paints4Trade product listing
Safety source	Current product label and Safety Data Sheet (SDS)

IMPORTANT

Always verify the current product page and Safety Data Sheet before specification or application.

Trade Paints technical advice should be sought where the intended use is outside the published product guidance.