

PRODUCT DATA SHEET

WaterSeal Brick Stone Sealer

Multi-Surface Clear UV Waterproofing Sealer



1 OVERVIEW

WaterSeal Multi-Surface Brick Stone Sealer is a clear, high-performance waterproofing treatment designed to help prevent water damage and resist mildew. Suitable for interior and exterior use, it forms a durable protective barrier while preserving the natural appearance of the treated surface.

2 APPLICATIONS & USES

- Brick, stone and concrete surfaces
- Driveways and garage floors
- Timber, wooden decking and fences
- Brush, roller or spray application
- Interior and exterior waterproofing protection

3 KEY BENEFITS

- Clear, non-yellowing finish
- Helps prevent water damage and mildew
- UV resistant for outdoor durability
- Suitable for multiple porous surfaces
- Long-lasting protective treatment

QUICK SPECIFICATION

Coverage	8-10 m ² /litre
Application	Brush / roller / spray
Finish	Clear / non-yellowing
Drying time	1-2 hours
Overcoating	4 hours
Brand	Trade Paints



KEY BENEFITS

- Multi-surface sealer
- Water damage protection
- UV resistant finish
- Interior & exterior use

TECHNICAL PRODUCT INFORMATION

PRODUCT INFORMATION (TYPICAL FIGURES)

Product name	WaterSeal Brick Stone Sealer
Brand	Trade Paints
Product type	Clear multi-surface UV resistant waterproofing sealer for porous household, garden and commercial surfaces
Recommended substrates	Brick, stone, concrete, driveways, garage floors, timber, wooden decking, fences and other suitable porous surfaces
Application methods	Brush, roller or spray
Coverage	Approx. 8-10 m ² per litre depending on porosity
Drying time	Approx. 1-2 hours
Overcoating time	Approx. 4 hours
Finish	Clear, non-yellowing
Recommended thinner / cleaner	Not stated on current product page
Available sizes	20 litre
MPN / SKU	SEAL/20

SURFACE PREPARATION

Detailed surface-preparation instructions are not stated on the current product page.

Prepare the substrate in accordance with the current product label and Safety Data Sheet.

For unfamiliar or previously treated surfaces, test a small area before full application.

APPLICATION GUIDANCE

Apply by brush, roller or suitable spray equipment.

Apply by brush, roller or spray. Coverage is approximately 8-10 m² per litre.

Coverage will vary depending on surface porosity.

Typical drying time is 1-2 hours with overcoating after approximately 4 hours.

Cleaning method is not stated on the current product page.

STORAGE

Storage conditions are not stated on the current product page. Follow the current product label and Safety Data Sheet for storage and handling requirements.

PRODUCT DATA SHEET

4 SAFETY PRECAUTIONS

- Use in well-ventilated areas
- Wear protective gloves and eye protection
- Avoid inhalation and contact with skin or eyes
- Keep out of reach of children

5 LIMITATIONS

This standardised sheet is compiled from the current Paints4Trade product listing for WaterSeal Brick Stone Sealer. The live product page, product label and Safety Data Sheet remain authoritative.

Coverage and drying figures are typical values and may vary with substrate porosity, environmental conditions and application method.

Detailed preparation, film thickness, cleaning and storage instructions are not stated on the current product page; refer to the current product label and Safety Data Sheet.

For unfamiliar, previously treated or non-standard surfaces, test compatibility before use.

6 REFERENCES & DOCUMENT CONTROL

Product	WaterSeal Brick Stone Sealer
Document reference	SEAL/20
Issue date	September 7, 2026
Primary source	https://paints4trade.com/waterseal-brick-stone-sealer-257390-p.asp
Product data basis	Current linked Paints4Trade product listing
Safety source	Current product label and Safety Data Sheet (SDS)

IMPORTANT

Always verify the current product page and Safety Data Sheet before specification or application.

Trade Paints technical advice should be sought where the intended use is outside the published product guidance.